

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : H04Q 7/00	A1	(11) International Publication Number: WO 92/03891 (43) International Publication Date: 5 March 1992 (05.03.92)
(21) International Application Number: PCT/US91/05120 (22) International Filing Date: 22 July 1991 (22.07.91) (30) Priority data: 568,112 16 August 1990 (16.08.90) US (71) Applicant: MOTOROLA, INC. [US/US]; 1303 East Algonquin Road, Schaumburg, IL 60196 (US). (72) Inventors: PEANA, Stefan ; 112 Palomino Circle, Boca Raton, FL 33487 (US). PINE, Jerrold, Scott ; 9555 Saddlebrook Drive, Boca Raton, FL 33496 (US). (74) Agents: INGRASSIA, Vincent, B./JG et al.; Motorola, Inc.-Intellectual Property Dept., 1500 N.W. 22nd Avenue, Boynton Beach, FL 33426 (US).		(81) Designated States: AT (European patent), BE (European patent), CA, CH (European patent), DE (European patent), DK, DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JF, KR, LU (European patent), NL (European patent), NO, SE (European patent). Published <i>With international search report.</i>

Best Available Copy

(54) Title: **PROGRAMMABLE ALERT FOR A COMMUNICATION DEVICE**



(57) Abstract

A communication device (100), comprises a receiver (103) for receiving a message, an alert generator (107) for presenting an alert, and a display (106) for displaying received messages and other information. The communication device (100) is capable of programming the alert using the display (106) for visual programming feedback, consequently displaying a musical staff and associated musical note representations.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU ⁺	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE*	Germany	MC	Monaco	US	United States of America
DK	Denmark				

+ Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.

PROGRAMMABLE ALERT FOR A COMMUNICATION DEVICE

5

Field of the Invention

This invention relates in general to the field of communication devices capable of displaying information and presenting alerts, and more specifically to those communication devices capable of programming the alerts.

Background of the Invention

A communication device (e.g., a selective call receiver), typically presents an alert to a user of the device using any combination of an audible alert, a visual alert, and a tactile alert. Typically, the audible alert comprises a constant tone frequency having a predetermined alert cadence and duration. The tactile alert, similarly, comprises a dominant frequency vibratory alert also having a predetermined alert cadence and duration. The conventional visual alert may be presented via a display or other visual indicating device (e.g., a light emitting diode (LED) or a lamp). Normally, a conventional light source with dominant frequency emissions in the visible light spectral range illuminates the display, the visual alert optionally flashing the visible information (i.e., "ON" and "OFF" pattern), in a predetermined cadence and duration.

Selective call receivers are such a part of our life today that an audible alert heard by a group of people having selective call receivers, does not clearly identify the intended receiving party of the message. Typically, confusion results causing a number of individuals to erroneously reach for their receivers which have not received a message.

This frustration is aggravated by the lack of programmability of alerts afforded the user of conventional selective call receivers. In those instances where the alert is programmable, it is programmed by the manufacturer either in the hardware configuration of the device or in the read-only-memory (ROM) of a controller within the communication device. Therefore, the user of the product is constrained to "standard"

alert choices, as programmed by the manufacturer of the communication device. Hence, the problem persists in contemporary communication devices.

5

Summary of the Invention

In carrying out one form of this invention, there is provided a communication device, comprising receiver means for receiving a message, alert means for presenting an alert, display means for
10 displaying the received messages and other information, and means for programming the alert using the display means for visual programming feedback.

15

Brief Description of the Drawings

FIG. 1 is a block diagram of an exemplary communication device (e.g., a selective call display receiver), in accordance with an embodiment of the present invention.

FIG. 2 is a front view of the selective call display receiver of FIG. 1.

20

FIG. 3A illustrates a 5 by 7 matrix capable of displaying representations of a musical staff and musical notes in accordance with the present invention.

FIG. 3B is an exemplary sixteen character display, illustrating musical notes to compose a custom alert.

25

FIG. 4 is a flowchart of an operational sequence according to one embodiment of the invention.

FIG. 5 is a block diagram of a programming computer interfacing with the communication device in an alternate embodiment of the present invention.

30

Description of a Preferred Embodiment

Referring to FIG. 1, a block diagram of a communication device 100 (e.g., a selective call display receiver) is shown, in accordance with an embodiment of the present invention. A battery (101) powered selective call receiver 100 operates to receive a signal via an antenna 102. The received signal is routed from the antenna 102 to a receiver 103. The receiver 103 demodulates the received signals using conventional techniques and forwards the demodulated signal to a control circuit 104, which decodes and recovers information contained within the received signal. In accordance with the recovered information and user operated controls (105), the selective call receiver presents at least a portion of the information, such as by a display 106, and signals the user via an audible or sensible alert 107 that a message has been received. The user may then view the information presented on the display 106.

The control circuit 104 shown in FIG. 1 preferably includes signal multiplexing integrated circuits, a microcomputer, a digital memory coupled to the microcomputer, environmental sensing circuitry such as for light or temperature conditions, audio power amplifier circuitry, control interface circuitry, and display illumination circuitry. These elements are arranged in a known manner which when assembled provides the display information receiver as requested by the customer.

Referring to FIG. 2, a front view of the selective call display receiver 100 of FIG. 1 illustrates two user operated controls 105 (e.g., two push buttons), capable of receiving alert programming information from the user of the communication device 100. The "up-arrow" user control 202 and the "right-arrow" user control 204 may be used to program the frequency, cadence, and duration of the audible alert, for example, as will be more fully discussed below.

Referring to FIGs. 3A and 3B, in this embodiment of the present invention the display 106 comprises 5 by 7 matrix cells 300, normally used to display character representations (e.g., numeric and/or alphanumeric characters), which may be part of the recovered information and presented as the received message. Each character displayed normally requires one 5 by 7 matrix cell 300. A couple of the seven row and five column display drivers (not shown) may selectively

illuminate a pixel 302 within a cell 300. Each pixel 302 illumination is typically controlled by a different pair of row and column drivers.

To program an exemplary audible alert in accordance with the invention, the illumination of the pixels 302 within the cell 300 may serve as visual programming feedback. Thus, the arrangement of pixels 302 and concatenated cells 300 (refer to FIG. 3B), in an exemplary sixteen character display 106 may mimic a musical composition, thereby visually aiding the programming of an audible alert into the selective call display receiver 100.

In this way, representations of a musical staff and musical notes may conform to the 5 by 7 matrix cell 300 arrangement. The musical notes on the musical staff may be represented by pixels 302 illuminated within the cell 300. For example, the lowest row pixels 304 may represent the musical note E and successive musical notes may be represented by increasingly higher row pixels 306 (e.g., F, G, A, B, C, and D), similar to a musical staff representation.

Additionally, each musical note may be represented by an illuminated pixel 302, and each pause or rest period may be represented by all darkened pixels for a particular column, where each column of pixels represents a time frame. Therefore, the concatenation of illuminated and darkened pixels mimic a musical composition, such as illustrated in FIG. 3B.

The two illustrated user operated controls (202 and 204) may be used to program the audible alert using the display 106 and musical note representations for visual programming feedback. The "up-arrow" user control 202 may serve to scroll through the musical note choices for a particular time frame. A flashing (e.g., blinking "ON" and "OFF" pattern) pixel 302 may indicate the current note for the time frame. To program the note the user may push and hold the user control 202 until the pixel 302 stops flashing. Once a note is selected for a particular time frame, the "right-arrow" user control 204 may advance to the next time frame. Advancing to the next time frame without programming a musical note in the current time frame preferably indicates a rest period or pause for the current time frame. Therefore, in this fashion the exemplary audible alert may be programmed into the communication device 100 using the display 106 for visual programming feedback.

Referring to FIG. 4, a flowchart of an exemplary alert programming sequence is shown, according to an embodiment of the present invention. Once the selective call display receiver 100 is turned "ON" and within a predetermined time interval thereafter, user controls 202 and 204 are monitored 400. In the preferred embodiment, if both user controls 202 and 204 are pushed and held, the selective call display receiver enters an audible alert programming mode 400. User control 202 is used to select the current note 402, and user control 204 advances to the next time frame on the musical staff representation 406, as described earlier. When both user controls (202 and 204) are pressed and held 404, the selective call display receiver exits the programming mode and emits the audible alert 408 (musical composition).

Referring to FIG. 5, a block diagram illustrates a programming computer 500 (e.g., a personal computer, a video display terminal, or other console), interfacing with the communication device 100 preferably via the control circuitry 104, in an alternate embodiment of the present invention. The programming computer 500 interfaces with the control circuitry 104 via a conventional connector (not shown) at the communication device 100. A conventional computer communication protocol (e.g., RS-232 and RS-422 protocol), may be used to send the alert programming information from the programming computer 500 to the communication device 100, with the display 106 providing visual programming feedback. In this inventive configuration, the user of the communication device 100 may enter the audible alert programming information using the programming computer 500, such as a personal computer, having the display 106 provide visual programming feedback.

In similar fashion to programming the audible alert, other types of alerts may be programmed. For example, the alert frequency, cadence, and duration for the tactile alert may be programmed accordingly. Similarly, the visual alert frequency, cadence, and duration may also be programmed at the communication device 100. Therefore, using the heretofore discussed invention the user of the communication device 100 is capable of effectively programming the alert at the communication device 100.

CLAIMS

1. A communication device, comprising:
receiver means for receiving a message;
5 alert means for presenting an alert;
display means for displaying the received messages and other
information; and
means for programming the alert using the display means for
visual programming feedback.
10
2. The device of claim 1, wherein the display means comprises a
liquid crystal display.
3. The device of claim 1, wherein the visual programming feedback
15 comprises a musical staff and associated musical note representations.
4. The device of claim 1, wherein the programming means
comprises at least one push button.
- 20 5. The device of claim 1, wherein the programming means
comprises an interface at the communication device capable of receiving
computer communication.
- 25 6. The device of claim 5, further comprising an external
programming computer capable of receiving alert programming
information and sending the alert programming information to the
communication device using computer communication at the interface.
7. The selective call receiver of claim 1, wherein the alert means
30 comprises an audible alert generator.
8. The selective call receiver of claim 1, wherein the alert means
comprises a tactile alert generator.
- 35 9. The selective call receiver of claim 1, wherein the alert means
comprises a visual alert indicator.

10. A method for programming an alert for a communication device having display means, comprising the steps of:
receiving an alert programming information at the
5 communication device; and
displaying the alert programming information using the display means.

11. The method of claim 10, wherein the displaying step further
10 comprises the step of displaying a musical staff and associated musical note representations.

12. The method of claim 10, wherein the receiving step comprises
15 the step of sensing a user input at the communication device.

13. The method of claim 10, wherein the receiving step comprises
the step of detecting computer communication at the communication device.

20 14. A selective call receiver, comprising:
a receiver for receiving a message;
an alert generator for presenting an alert;
a display for displaying the received messages and other
information; and
25 means for programming the alert using the display means for visual programming feedback.

15. The selective call receiver of claim 14, wherein the display
30 comprises a liquid crystal display.

16. The selective call receiver of claim 14, wherein the visual
programming feedback comprises a musical staff and associated musical
note representations.

35 17. The selective call receiver of claim 14, wherein the programming means comprises at least one push button.

18. The selective call receiver of claim 14, wherein the programming means comprises an interface at the communication device capable of receiving computer communication.

5

19. The selective call receiver of claim 18, further comprising an external programming computer capable of receiving alert programming information and sending the alert programming information to the communication device using computer communication at the interface.

10

20. The selective call receiver of claim 14, wherein the alert generator comprises an audible alert generator.

21. The selective call receiver of claim 14, wherein the alert generator comprises a tactile alert generator.

15

22. The selective call receiver of claim 14, wherein the alert generator comprises a visual alert indicator.

23. A communication device, comprising:
a receiver for receiving a message;
an alert generator for presenting an alert;
a display for displaying received messages and other information;

5 and

means for programming the alert using the display for visual programming feedback, consequently displaying a musical staff and associated musical note representations.

1/2




FIG. 1




FIG. 5







FIG. 2

2/2

**FIG. 3A****FIG. 3B****FIG. 4**

INTERNATIONAL SEARCH REPORT

International Application No. PCT/US91/05120

I. CLASSIFICATION OF SUBJECT MATTER	
According to International Patent Classification (IPC) and both National Classification and IPC	
IPC(5): H04Q 7/00	
US CL : 3407825.44	
FIELDS SEARCHED	
Minimum Documentation Searched	
Classification Symbols	
US	340/825.44, 825.45, 825.46, 825.47, 825.48, 311.1 84/477R, 488, 464R, 464A, 609
Documentation Searched other than Minimum Documentation to the extent that such documents are included in the Fields Searched	

II. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No. 1
Y	US, A, 4,368,989 (KAWASHIMA) 18 JANUARY 1983 See abstract; col. 1, lines 43-70; figs. 5a-5d col. 6, lines 11-43.	1-23
Y	US, A, 4,868,561 (DAVIS) 19 SEPTEMBER 1989 See col. 2, line 60 to col. 3, lines 25 col. 5, lines 1-3 and claim 5.	1-23
Y	US, A, 4,388,000 (HAGIHARA) 14 JUNE 1983 See entire document.	1-23
A	JP, A, 1-321484 (NAKADA) 27 DECEMBER 1989 See abstract.	1-23

- * Special categories of cited documents:
 - "A" document defining the general state of the art which is not considered to be of particular relevance
 - "E" earlier document but published on or after the international filing date
 - "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
 - "O" document referring to an oral disclosure, use, exhibition or other means
 - "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step
- "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "A" document member of the same patent family

IV. CERTIFICATION
Date of the Actual Completion of the International Search

22 OCTOBER 1991
International Searching Authority
ISA/US

Date of Mailing of this International Search Report

18 NOV 1991

Signature of Authorized Officer
PETER WEISSMAN

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

This Page Blank (uspto)